Subbi

forming bit line patterns on a substrate including word line patterns, thereby forming a first resulting structure;

- b) \ forming an interlayer insulating layer on the first resulting structure;
- c) etching the interlayer insulating layer with an etching mask defining a straight line shape, and forming a straight line shaped contact opening between neighboring bit line patterns; and
 - d) forming insulating layers on sidewalls of the bit line patterns.

BF

6. (Amended) A method of claim 1, wherein top surfaces of the bit line patterns are covered with a layer selected from a group consisting of a silicon nitride layer, a silicon oxynitride layer, and an oxide layer.

A3

8. (Amended) The method of claim 7, wherein in step c), the interlayer insulating layer is etched by using a gas selected from a group consisting of Ar, O_2 , N_2 , H_2 , CH_4 , C_2H_4 , and C_xF_y .

REMARKS

By the present Amendment, Applicants cancel claims 10-20 without prejudice or disclaimer of the subject matter thereof, and amend claims 1, 6, and 8. Thus, claims 1-9 are pending.

In the Office Action, the Examiner objected to claims 1, 6, and 16 for containing informalities; rejected claims 8 and 18 under 35 U.S.C. § 112, second paragraph, for containing informalities; rejected claims 1-3 and 11-13 under 35 U.S.C. § 102(e) as anticipated by Duane et al., U.S. Patent No. 6,329,695 ("Duane"); rejected claims 11 and 16 under 35 U.S.C. § 102(b) as anticipated by Cooper et al., U.S. Patent No.

FINNEGAN HENDERSON FARABOW GARRETT & DUNNER LLP

1300 I Street, NW Washington, DC 20005 202.408.4000 Fax 202.408.4400 www.finnegan.com